

# CASIO®

# CORE SERIES

## THE COST-EFFICIENT ENTRY

XJ-V10X | XJ-V100W | XJ-V110W



Core Series

The new Core Series with 1.5x zoom lens is the ultimate solution for getting started with less expensive, mercury-free projection. The revolutionary laser and LED hybrid light source also cuts operating costs in everyday use: despite the impressive brightness of up to 3,500 AL and a contrast of 20,000:1, it consumes as much as 40% less electricity than conventional projectors. And with a service life of up to 20,000 hours, it is especially durable.

 **LampFree**  
GO LAMP FREE AND SAVE



New mercury-free light source



Up to 20,000h life time

**Direct ON/OFF**



Brilliant colour rendition



Up to 3,500 ANSI-lumens



Eco

**HDMI**

**<0.5 Watt**  
per hour (Standby)



Made in Japan

All details at: [www.casio-projectors.eu](http://www.casio-projectors.eu)

## Technical specifications of the Core series at a glance:

		XJ-V10X	XJ-V100W	XJ-V110W
Display	Technology: Resolution:	0.55" DLP® chip (XGA) 1,024 x 768 pixels (XGA)	0.65" DLP® chip (WXGA) 1,280 x 800 pixels (WXGA)	
Illumination technology	Type: Service life: Brightness:	Laser and LED hybrid technology Up to 20,000 hours 3,300 AL		
Picture	Contrast: Colour depth:	20,000:1 Up to 1.07 billion (full colour)		
Projection lens	Technology: Projection ratio (viewing distance:width): Offset: Min. distance: Focus:	1.5x optical zoom 1.66-2.42:1 50% 0.83 m Manual		
Projection	Size of the projection screen: Viewing distance 60" screen: Viewing distance 100" screen:	30" (0.76 m) to 300" (7.62 m) 1.95 m to 2.87 m 3.33 m to 4.85 m	35" (0.89 m) to 300" (7.62 m) 1.64 m to 2.42 m 2.81 m to 4.11 m	
Keystone correction	Vertical (manual): Vertical (automatic):	+30°/±30° +30°		
Interfaces	Computer: Digital input: Audio:  Control inputs: Other/further inputs:	1 x 15-pin D-Sub (VGA) HDMI port Input terminal: 3.5 mm stereo mini jack x1 Output terminal: 3.5 mm stereo mini jack x1 (variable audio input) RS-232C Micro-USB type B: firmware update		
Extended functions		Direct power on, direct power off, rear projection, freeze, blank screen, ceiling mounting, (4x M4), digital zoom (2x), presentation timer, password protection feature		
Operating noise		Light Control On (1-7): 29-35 dB Light Control Off (Normal/Bright): 36.5 dB/39 dB		
Energy consumption	Light Control On (Light Output 1-7): Light Control Off (Normal/Bright): Standby:	75-145 W 155 W/180 W	60-125 W 135 W/150 W	80-155 W 165 W/190 W 0.23 W
Computer compatibility	Max. resolution (compressed):	Computer: 1,920 x 1,200 pixels (VGA) Digital input: 1,920 x 1,080 pixels (Full HD 1080p)		
Included with product		Mains cable, IR remote controls (YT-150), quick guide, warranty card		
General	Dimensions (W x H x D): Weight: Casing/colour: Operating temperature: Warranty:	299 x 97 x 299 mm 3.5 kg White 5-35°C 1. When used for less than 12 hours per day: Projector: three years Light source: five years or 10,000 hours <sup>1</sup> 2. When used continuously for more than 12 hours per day: Projector: two years Light source: two years or 6,000 hours <sup>1</sup>		

816PVP-KF-CORE-I-EU



The DLP® logo is a registered trademark of Texas Instruments.



High-Definition Multimedia Interface is a trademark or registered trademark of HDMI Licensing, LLC.



<sup>1</sup> Whichever is reached first.